

Appearance

/ The worldwide popular, great-circle, streamlined surface modeling is applied, with smooth, beautiful, and elegant appearance.

Stability

/ The broad and solid chassis and steady reach mechanism, as well as the drive unit that is fixed at center, realize low gravity center, and guarantee sufficient stability of the truck.

Flexibility

/ The driving system that is located at rear part of chassis uses EPS (Electric Power Steering) technology, features low-speed and large torque. The 180-degree steering mode of standard configuration, make the truck flexible and convenient, and allow it turn easily even in confined space.

Comfort


- / Operating levers of ergonomic design, integrated console, all important operating parts are within the reach of your hands.
- / The mast of optimized design with wide view avoids blocking the sight of the operator, and large size of the fork shelf offers wider view.
- / The seat can be adjusted forward and backward, also with the function of vibration reduction.
- / The truck body with increased width and height offers larger operating space for hands and legs of the operator.
- / The new designed overhead guard structure allows the operator to observe the movement of load more clearly.

Maintenance

- / The fully-opened cover provides easy maintenance for motor, controller and transmission, braking, and hydraulic systems.
- / The battery compartment can be removed forward, so replacement or maintenance is very easy.



Wider view OHG



High-performance motor



Comfortable and convenient seat



Instrument can display the steering angle and direction Synchronously



The steering wheel is extensible, so the operator can choose the best driving position



ZHEJIANG HANGCHA IMP. &EXP. CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com
www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



ISO14001
ISO14001:2015



ISO9001
ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

2019 VERSION ZCOPYRIGHT 2019/11



INNOVATIVE LITHIUM-ION

A Series Reach Truck

with capacities of 1,200 to 2,000kg

The World of Hangcha



LI-ION POWERED



HANGCHA provides Li-Ion battery (LiFePO₄) with 5 years or 10000 hours warranty.




**5 YEARS
WARRANTY**

INNOVATIVE SOLUTIONS NEW POWER NOW

Innovative, reliable lithium-ion technology (Lithium Iron-Phosphate), which are developed jointly by HANGCHA and CATL. Battery cells and modules are from CATL, with reliable quality, exclusively for HANGCHA.

- / We use square lithium iron phosphate batteries and modules used in large quantities by commercial vehicles in mature economies.
- / The module uses an aluminum alloy frame which is sturdy, lightweight and with excellent heat dissipation.
- / Safe and effective: Charging efficiency as high as 98%, thermal runaway temperature 600 °C or above.
- / Adapted to low temperatures: Comes standard with an electrical heating feature, ensuring normal operation in low temperatures.
- / Quick charging: Can charge and operate at the same time, fully charged in 2 hours.
- / Long-working: 4000 charging cycles, capacity retention greater than 80%.
- / Maintenance-free: Battery does not require manual maintenance.
- / Green and clean: Pollution-free, zero emissions.



Li-Ion
**2 hours
100%**

Lead-acid batteries
8-10 hours 100%

Rapid charging and opportunity charging ensure continuous availability of vehicles.

Li-Ion powered forklifts are always available. They allow for fast full charging or boost charging (100 % charge in 2 hours). They are maintenance free and do not require a battery change when used for multi-shift operations.

Li-Ion Battery Pack specification

Type		CQD16-AC4-I	CQD18-AC4-I	CQD20-AC4-I
Li-Ion battery	V/Ah	80/271	80/271	80/271
Titans charger		SLC-80100	SLC-80100	SLC-80100

A Series Reach Truck

The reach truck is suitable for working in narrow passageway and confined space, with high lifting and load capacity, and is the ideal tool for loading, unloading, handling, and stacking in warehouse, supermarket, and workshop.

**Environment/
Efficiency/
Economy**

Reliability & Safety

- / Major electrical components such as controller, contactor, and power plug are all of foreign famous brands.
- / As a standard configuration, the emergency power off switch complies with European safety standards.
- / Electronic and hydraulic overload protection, power-failure lock up of fork(optional), and safe pedal.

Benefits of the AC Power System

- / The AC power system has high efficiency, full protection functions, powerful acceleration performance, sensitive and fast steering.
- / The brushless, maintenance-free AC motor has longer service life, and lower maintenance cost.


Advance

- / Three-phase AC technology is applied for driving and steering, AC technologies are available for lifting. Full AC power system has higher efficiency, and is free maintenance.
- / The MOSFET integrated controller guarantees smooth and accurate control on driving, steering and lifting, as well as superior speed regulation performance, with regenerative braking, reverse braking, anti-slipping on slope and other functions, resulting in more efficient, safer operations.
- / The LCD battery condition meter, timer, fault self-diagnosis meter, and display can not only display most important operating data, driving direction and location of driving wheels that are interactive with steering, but also realize accurate display in harsh environment.
- / The full AC truck is equipped with non-backlash, high pressure resistant, silent gear pump.
- / The full AC truck is equipped with stepless speed regulation for lifting operation, the mast lift top buffering, mast move forward/backward buffering, travelling speed and speed of mast move forward/backward will slow down automatically when the mast lifting high position, all of this can greatly improve the stability of the truck.
- / The CANBUS communication technology is applied to monitor motor speed, temperature, and other information in real time, realizing closed-loop control.
- / The truck has a triple braking mechanism, i.e. electronic braking (reverse regenerative braking), front wheel hydraulic braking, and electromagnetic parking braking.



High-performance Mast

- / The operator has wider view in the load direction.
- / Built-in sideshifter and fork tilting are standard configuration.
- / The mast made with imported steel channels and compact structural design has a maximum lifting height: 12500mm.
- / Height monitoring and lifting height limitation system are optional.







Battery can be removed forward, easy for maintenance

Traction device

A Series Reach Truck

Distinguishing mark	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.				
	1.2	Manufacturer's type designation		CQD12-AC4 CQD12-AD2	CQD14-AC4 CQD14-AD2	CQD16-AC4 CQD16-AD2	CQD18-AC4 CQD18-AD2	CQD20-AC4 CQD20-AD2
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		electric	electric	electric	electric	electric
	1.5	Rated capacity/rated load	Q (kg)	1200	1400	1600	1800	2000
	1.6	Load centre distance	c (mm)	600	600	600	600	600
	1.8	Load distance, centre of drive axle to fork	x (mm)	325	325	235	235	305
	1.8.1	Load distance, centre of drive axle to fork,mast reached forward	x1 (mm)	183	183	183	213	213
	1.9	Wheelbase	y (mm)	1480	1480	1480	1480	1550
	Weight	2.1	Service weight (including battery)	Kg	3130	3130	3320	3330
Tyres, chassis	3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane		polyurethane	polyurethane	polyurethane	polyurethane	polyurethane
	3.2	Tyre size, front	mm	Ø343×114	Ø343×114	Ø343×114	Ø343×135	Ø343×135
	3.3	Tyre size, rear ×2	mm	Ø285×100	Ø285×100	Ø285×100	Ø343×108	Ø343×108
	3.5	Wheels,number front/rear(×=driven wheels)		1×2	1×2	1×2	1×2	1×2
	3.7	Tread width,rear	b11(mm)	1136	1136	1136	1144	1144
Dimensions	4.1	Tilt of mast/fork carriage forward/backward	α(B°)	2/4	2/4	2/4	2/4	2/4
	4.2	Height, mast lowered	h1 (mm)	2100	2100	2100	2100	2100
	4.4	Lift	h3 (mm)	3000	3000	3000	3000	3000
	4.7	Height of overhead guard	he (mm)	2240	2240	2240	2240	2240
	4.10	Height of support arms	he(mm)	305	305	305	361	361
	4.19	Overall length	l1(mm)	2463	2463	2553	2553	2553
	4.20	Length to face of forks	l2 (mm)	1393	1393	1483	1483	1483
	4.21	Overall width	b1/b2(mm)	1270/1270	1270/1270	1270/1270	1286/1270	1286/1270
	4.22	Fork dimensions ISO	s/e/l (mm)	40×122×1070	40×122×1070	40×122×1070	40×122×1070	40×122×1070
	4.25	Distance between fork-arms	bs (mm)	244-882	244-882	244-882	244-882	244-882
	4.28	Reach distance	ls (mm)	508	508	418	448	518
	4.34.1	Aisle width for pallets 1000 x 1200 crossways	Ast (mm)	2838	2838	2907	2907	2922
	4.34.2	Aisle width for pallets 800 x 1200 lengthways	Ast (mm)	2897	2897	2980	2980	2984
	4.35	Turning radius	Wa (mm)	1735	1735	1735	1735	1804
	Performance data	5.1	Travel speed,laden/unladen	Km/h	10.2/10.2	10.2/10.2	10.2/10.2	10.2/10.2
5.2		Lift speed,laden/unladen	m/s	0.400/0.530	0.390/0.530	0.370/0.530	0.340/0.530	0.310/0.530
5.3		Lowering speed,laden/unladen	m/s	0.420/0.480	0.420/0.480	0.420/0.480	0.420/0.480	0.420/0.480
5.8		Max. gradeability,laden/unladen	%	12/15	12/15	11/15	10/15	10/15
6.1		Drive motor rating S2 60 min	kW	AC 6.5	AC 6.5	AC 6.5	AC 6.5	AC 6.5
Electric- engine	6.2	Lift motor rating at S3 15%	kW	AC 12.8	AC 12.8	AC 12.8	AC 12.8	AC 12.8
		Steering motor	kW	AC 0.67	AC 0.67	AC 0.67	AC 0.67	AC 0.67
	6.4	Battery voltage, nominal capacity K5	V/Ah	48/400	48/400	48/500	48/500	48/500
	6.5	Battery weight	kg	666	666	855	855	855
Addition data	8.1	Type of drive control	CURTIS Full AC / INMOTION Full AC					
	10.1	Operating pressure for attachments	bar	140	140	165	185	210
	10.7	Sound level at the driver's ear according to EN / DIN 12 053	dB (A)	<75	<75	<75	<75	<70



1.2t-2.0t Mast specification

Type	Model	Lifting height h3	Mast lowered h1	Mast extended h4		Free lifting height h2		Tilting range		Load center@600mm				
				Without backrest	With backrest	Without backrest	With backrest	Forward	Backward	1.2t	1.4t	1.6t	1.8t	2.0t
Wide view duplex mast	QA20B	mm	mm	mm	mm	mm	mm	(°)	(°)	kg	kg	kg	kg	kg
		2700	1950	3355	3665	340	340	2	4	1200	1400	1600	1800	2000
		3000	2100	3655	3965	340	340	2	4	1200	1400	1600	1800	2000
		3300	2250	3955	4265	340	340	2	4	1200	1400	1600	1800	2000
		3500	2350	4155	4465	340	340	2	4	1200	1400	1600	1800	2000
		3600	2400	4255	4565	340	340	2	4	1200	1400	1600	1800	2000
		4000	2650	4655	4965	340	340	2	4	1200	1400	1600	1800	2000
		4300	2790	4955	5265	340	340	2	4	1200	1400	1600	1800	2000
		4500	2900	5155	5465	340	340	2	4	1200	1400	1600	1800	2000
		4800	3095	5495	5765	340	340	2	4	1200	1400	1600	1800	2000
		5000	3195	5695	5965	340	340	2	4	1200	1400	1600	1800	2000
		4300	2085	4987	5265	1376	1120	2	4	1200	1400	1600	1800	2000
		4500	2165	5170	5465	1495	1200	2	4	1200	1400	1600	1800	2000
		4800	2265	5470	5765	1595	1300	2	4	1200	1400	1600	1800	2000
		5000	2315	5670	5965	1596	1350	2	4	1200	1400	1600	1800	2000
Full free triplex mast	QA20V (imported steel)	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
		5500	2490	6170	6465	1796	1525	2	4	1200	1400	1600	1800	2000
		6000	2665	6670	6965	1995	1700	2	4	1200	1400	1600	1800	2000
		6500	2835	7170	7465	2136	1870	2	4	1200	1300	1500	1700	1900
		7000	3020	7670	7965	2350	2055	2	4	1200	1200	1400	1600	1800
		7500	3180	8170	8465	2510	2215	2	4	1100	1100	1300	1500	1700
		8000	3350	8670	8965	2680	2385	2	4	1000	1000	1200	1400	1600
		8500	3580	9170	9465	2910	2615	2	4	900	900	1100	1300	1500
		9000	3800	9670	9965	3130	2835	2	4	800	800	1000	1200	1400
		9500	3970	10170	10465	3300	3005	2	4	700	700	900	1100	1300
		10000	4100	10670	10965	3430	3135	2	4	600	600	800	1000	1200
		10500	4250	11170	11465	3580	3285	2	4	500	500	700	900	1100
		11000	4450	11670	11965	3780	3485	2	4	400	400	600	800	1000
		11500	4700	12170	12465	4030	3735	2	4	250	250	450	650	850
		12000	4900	12670	12965	4230	3935	2	4	100	100	300	500	700
		12500	5150	13170	13465	4480	4185	2	4	\	\	150	350	550

$$Ast=Wa+R+a=Wa+\sqrt{(l_6-x)^2+(\frac{b_{12}}{2})^2}+a$$

