

5-7t X series mast:(penumatic)

Type	Model	Max. fork height	Overall height				Free lift		Load distance, centre of drive axle to fork	Tilt range	Capacity		
			Lowered	Extended		w/without backrest	w/ith backrest	Load capacity at 600mm					
				w/without backrest	w/ith backrest			Dual tire					
								5t			6t	7t	
		mm	mm	mm	mm	mm	mm	mm	(°)	kg	kg	kg	
Wide view mast	XR50/70M250	2500	2250	3495/3667	3907	160	160	600/605	10/12	5000	6000	7000	
	XR50/70M270	2700	2350	3695/3867	4107	160	160	600/605	10/12	5000	6000	7000	
	XR50/70M300	3000	2500	3995/4167	4407	160	160	600/605	10/12	5000	6000	7000	
	XR50/70M330	3300	2650	4295/4467	4707	160	160	600/605	10/12	5000	6000	7000	
	XR50/70M360	3600	2800	4595/4767	5007	160	160	600/605	10/12	5000	6000	7000	
	XR50/70M400	4000	3000	4995/5167	5407	160	160	600/605	10/12	5000	6000	7000	
	XR50/70M430	4300	3200	5300/5467	5707	160	160	600/605	6/6	5000	6000	7000	
	XR50/70M450	4500	3300	5500/5667	5907	160	160	600/605	6/6	5000	6000	7000	
	XR50/70M480	4800	3450	5800/5967	6207	160	160	600/605	6/6	5000	6000	7000	
	XR50/70M500	5000	3550	6000/6167	6407	160	160	600/605	6/6	5000	6000	7000	
	XR50/70M550	5500	3850	6550/6667	6907	160	160	600/605	6/6	4750	5700	6600	
	XR50/70M600	6000	4100	7050/7167	7407	160	160	600/605	6/6	4400	5400	6400	
Wide view mast Full free Duplex mast	XR50/70U250	2500	2185	3455/3615	3637	1230/1070	1048	631/636	10/12	5000	6000	7000	
	XR50/70U270	2700	2300	3655/3815	3837	1345/1185	1163	631/636	10/12	5000	6000	7000	
	XR50/70U300	3000	2450	3955/4115	4137	1495/1335	1313	631/636	10/12	5000	6000	7000	
	XR50/70U330	3300	2600	4255/4415	4437	1645/1485	1463	631/636	10/12	5000	6000	7000	
	XR50/70U360	3600	2750	4555/4715	4737	1795/1635	1613	631/636	10/12	5000	6000	7000	
Wide view mast Full free Triplex mast	XR50/70U400	4000	2950	4955/5115	5137	1995/1835	1813	631/636	10/12	5000	6000	7000	
	XR50/70N450	4500	2725	5735	5907	1500	1328	667/672	6/6	4500	5500	6400	
	XR50/70N480	4800	2825	6035	6207	1600	1428	667/672	6/6	4500	5500	6300	
	XR50/70N500	5000	2875	6213	6407	1672	1478	667/672	6/6	4500	5500	6300	
	XR50/70N550	5500	3075	6785	6907	1800	1678	667/672	6/6	4200	5200	6100	
	XR50/70N600	6000	3225	7235	7407	2000	1828	667/672	6/6	4000	5000	5500	
	XR50/70N700	7000	3675	8385	8407	2300	2278	667/672	6/6	3000	3300	3800	

